



Features:

- Low Insertion Loss
- Good reliability and stability
- Polishing type: PC, UPC, and APC
- Various interfaces: FC, SC, ST, LC...
- Core of cable: 4, 6, 8, 12, 24...
- These Single mode 12 fiber pigtails with 900 micron buffer are ready for splicing.
- Each fiber strand in the kit has a color-coded buffer for easy identification and the colors are industry standard.
- In this 12-pack, twelve strands of fiber are terminated on one end with SC connectors.
- Connectors are ceramic with Ultra physical contact (UPC) finish. Each cable comes with test results and a lifetime guarantee.

Description:

12 Strand 9/125 Fiber Optic Pigtail 1.2m SC/UPC Single Mode, 12 fiber pigtail, OEM & ODM Custom made.

Technical Parameters:

Parameter:	Single mode	Multi mode(optional)
Insertion Loss	➤ ≤0.3dB	➤ ≤0.20dB
Return Loss	➤ ≥45 dB (PC) ➤ ≥50 dB (UPC) ➤ ≥60 dB (APC)	➤ ≥35 dB (PC) ➤ ≥45 dB (UPC)
Wavelength	➤ 1310nm, 1550nm	➤ 850nm, 1310nm
Repeatability	➤ ≤0.1	
Durability	➤ ≤0.2 dB typical change, 1000 matings	
Interchangeability	➤ ≤0.2dB	
Cord diameter	➤ 3.0mm	
Connector Available	➤ SC, FC, ST, LC, MU, MTRJ	
Fiber core available	➤ 4, 6, 8, 12, 24 fiber...	