



Features:

- Low Insertion Loss
- Good reliability and stability
- These Single mode 12 fiber pigtails with 900 micron buffer are ready for splicing.
- Each fiber strand in the kit has a color-coded buffer for easy identification and the colors are industry standard.
- In this 12-pack, twelve strands of fiber are terminated on one end with FC connectors.
- Connectors are ceramic with ultra physical contact (UPC) finish. Each cable comes with test results and a lifetime guarantee.

Description:

12 Fiber optic pigtail 9/125 1.2m FC/UPC Single Mode.

Fiber pigtails are a great solution for fusion splicing inside of a fiber optic enclosure. The ribbon fan-out fiber pigtails come with a partial outer jacket to help protect the tight buffer fibers from being damaged. If space is a premium, the outer jacket can easily be removed, allowing the pigtails to have a tighter bend radius and take up less space.

Technical Parameters:

Parameter:	Single mode	Multi mode(optional)
• Insertion Loss	➤ ≤0.3dB	➤ ≤0.20dB
• Return Loss	➤ ≥45 dB (PC) ➤ ≥50 dB (UPC) ➤ ≥60 dB (APC)	➤ ≥35 dB (PC) ➤ ≥45 dB (UPC)
• Wavelength	➤ 1310nm,1550nm	➤ 850nm,1310nm
• Repeatability	➤ ≤0.1	
• Durability	➤ ≤0.2 dB typical change, 1000 matings	
• Interchangeability	➤ ≤0.2dB	
• Cord diameter	➤ 3.0mm	
• Connector Available	➤ SC,FC,ST,LC,MU,MTRJ	
• Application	➤ Telecommunication Network ➤ Testing Equipment ➤ Local Ares Network ➤ CATV	
• Fiber core available	➤ 4,6,8,12,24 fiber...	

