

10/100/1000M 2 1.25G fiber port and 4 10/100/1000M POE

P/N: ITT-MC4366



The ITT-MC4366 is a POE switch designed for network monitoring. It has four 10/100/1000Mbps Ethernet ports and two 1.25Gbps fiber ports. It is designed with imported Marvell chip to achieve lower power consumption and high stability. It extends the transmission distance of a network from 100m to 120km via copper cables. There are also many other advantages such as isolation protection, good data security, working stability and easy maintenance.

### Features:

- Support the switch between 10/100/1000Base-TX and 1000Base-SX/LX
- 2\*1.25Gbps full-duplex fiber ports and 4\*1000M Ethernet port with auto-negotiation function
- Support 1000M speed rate, MDI/MDIX and half/full-duplex with auto-negotiation function
- Each port has the complete LED Indicator light
- Support single mode single fiber, single mode dual fiber, multi-mode dual fiber and SFP slot
- Support 1d Spanning Tree
- Support high performance QoS function on each port
- Support broadcast storm control
- Support 48-56V voltage input
- Support 8K MAC table
- Support IEEE802.3x flow control and back pressure control
- Require no configuration and will instantly operate as soon as you power it up
- Small volume, light weight
- Low power consumption chip with heat sink built in to ensure longtime efficient operation
- Support POE power up to 30W for each port, support IEEE802.3af, IEEE802.3at

SERVICES:  
Guaranteed Warranty



## Interface:

<b>Standards</b>	<ul style="list-style-type: none"> <li>➤ IEEE802.3 10Base-T</li> <li>➤ IEEE802.3u 1000Base-TX/FX</li> <li>➤ IEEE802.3x Flow control</li> <li>➤ IEEE802.3z 1000Base-SX/LX</li>   <li>➤ IEEE802.3af</li> <li>➤ IEEE802.1p QoS</li> <li>➤ IEEE802.1d Spanning Tree</li> <li>➤ IEEE802.3at</li> </ul>
<b>Ethernet Port</b>	<ul style="list-style-type: none"> <li>➤ Connector: RJ45</li> <li>➤ Data Rate: 10/100/1000M</li> <li>➤ Distance: 100m</li> <li>➤ UTP Type: UTP-5E or higher level</li> </ul>
<b>Fiber Port</b>	<ul style="list-style-type: none"> <li>➤ Connector: SFP slot</li> <li>➤ Data Rate: 1.25Gbps</li> <li>➤ Optical wavelength: 850nm/1310nm/1490nm/1550nm</li> <li>➤ Distance: 550m ~ 100km</li> </ul>
<b>POE</b>	<ul style="list-style-type: none"> <li>➤ Power type: end span</li> <li>➤ Cell: 1/2+, 3/6-</li> <li>➤ Port characteristics: 15.4W/30W</li> <li>➤ Power supply: 65W</li> </ul>
<b>Power</b>	<ul style="list-style-type: none"> <li>➤ Power type: external power supply</li> <li>➤ Input Voltage: AC100V ~ 240V 50 / 60Hz</li> <li>➤ Connector: DC Socket</li> <li>➤ Working Voltage: 48-56V</li> <li>➤ Power Consumption: 1.4W ~ 3.0W</li> </ul>
<b>Work Environment</b>	<ul style="list-style-type: none"> <li>➤ Storage Temperature: -40 ~ 70°C</li> <li>➤ Operating Temperature: -10 ~ 55°C</li> <li>➤ Relative Humidity: 5-90% (no condensation)</li> </ul>
<b>Physical Characteristics</b>	<ul style="list-style-type: none"> <li>➤ Dimension: 160×84×26mm</li> <li>➤ Weight: 0.30kg</li> <li>➤ Color: Metal, Black</li> </ul>
<b>Certifications:</b>	<ul style="list-style-type: none"> <li>➤ CE, FCC, RoHS</li> </ul>

SERVICES:  
Guaranteed Warranty

