



## Description:

The ITT-MU8599 is the point-to-point optical transmission device developed on the basis of VLSI. The device provides 1-16\*E1 interface, 1-4\*10/100/1000M Ethernet interface (Wire Speed 1000M) and 2 expansion interfaces. 4\* Ethernet interface is switch interface, can support VLAN. 1 expansion interface can be used as the transmission channel of RS232/RS485/RS422 asynchronous data, dry contact signal, 1Channel digital business phone can be optional. It is very flexible. It has alarm function. The work is reliable, stable, and low power consumption, high integration, small size.

### ◆ Fiber

#### Multi-mode Fiber

- Multi-mode Fiber
- 50/125um, 62.5/125um,
- Maximum transmission distance: 5Km @ 62.5 / 125um single mode fiber,attenuation (3dbm/km)
- Wave Length: 820nm
- Transmitting power:12dBm (Min) ~-9dBm (Max)
- Receiver sensitivity: 28dBm (Min)
- Link budget:16dBm

#### Single-mode Fiber

- 8/125um, 9/125um
- Maximum transmission distance: 40Km
- Transmission distance: 40Km @ 9 / 125um single mode fiber, attenuation (0.35dbm/km)
- Wave Length: 1310nm
- Transmitting power: 9dBm (Min) ~-8dBm (Max)
- Receiver sensitivity: 27dBm (Min)
- Link budget: 18dBm

## Features:

- Based on self -copyright IC
- The Fiber bandwidth is up to 1.5G, Ethernet bandwidth is Wire Speed 1000M
- Ethernet interface rate is 10/100/1000M, half/full duplex Auto-Nego
- 4\*Ethernet interface is switch interface, support VLAN, can set to 4 channel logical isolation
- Provide Console manage interface (RS232)
- Provide two fiber interface 1+1 protect (APS) function
- E1 interface comply with G.703, adopts digital clock recovery and smooth phase-lock technology
- Uses standard 2 wire telephone (non-telephone handles) set as engineering order-wire hotline(optional)
- When optical lose signal, it can detect the remote device is power off or fiber is disconnected, and indicates alarm by LED
- The local device can view the remote device working condition
- Provide 2 expansion interface, you can extend 1~2Channel asynchronous data, such as RS232/RS485/RS422/Manchester code;
- Provide command the remote interface Loop Back, support local E1 Loop Back function, support E1 LOS and AIS alarm ,ease line maintenance
- The transmission distance is up to 2-100Km without interruption
- Support SNMP manager (SNMP agent inside)
- AC 220V, DC-48V, DC24V can be optional
- DC-48V/DC24V power supply polarity detection function, Polarity-Free

### ◆ Gigabit Ethernet Interface (10/100/1000M)

- Interface rate: 10/100 /1000Mbps, half/full duplex auto-negotiation
- Interface Standard: Compatible with IEEE 802.3, IEEE 802.1Q (VLAN)
- MAC Address Capability:4096
- Connector: RJ45, support Auto-MDIX

### ◆ Working environment

- Working temperature: -10°C ~ 50°C
- Working Humidity: 5%~95 % (no condensation)
- Storage temperature: -40°C ~ 80°C
- Storage Humidity: 5%~95 % (no condensation)

◆ **E1 Interface**

- Interface Standard: comply with protocol G.703;
- Interface Rate: n\*64Kbps±50ppm;
- Interface Code:HDB3;
- E1 Impedance:75Ω (unbalance), 120Ω (balance);
- Jitter tolerance:In accord with protocol G.742 and G.823
- Allowed Attenuation:0~6dBm

**Technical Parameters:**

• <b>Functional Description</b>	➤ 16E1+4GE PDH 19"inch 1U, Optional(order wire phone, Console, SNMP 1+1 Back up Optic fiber
• <b>Port Description</b>	➤ two optical interface 1+1 port, 16*E1 interfaces (75/120 ohms), 4*GE interfaces,1*RS232 Console interface,1*SNMP Ethernet interface, one engineering order-wire telephone interface
• <b>Power</b>	➤ Power supply: AC180V ~ 260V; DC -48V; DC +24V ➤ Power consumption: ≤15W
• <b>Dimension</b>	➤ Product Size: 19 inch 1U 483X138X45mm(WXDXH)
• <b>Weight</b>	➤ 3.0KG

