

SHDSL SA 2ETH 2E1

P/N: ITT-TM161



## Introduction



The ITTelecom SHDSL product family offers a broad range of products, which are based on the latest SHDSL standards (ITU-T G.991.2 & ETS TS 101524), while also being fully interoperable with all our existing SHDSL equipment. The Ittelecom supports beside of the standardized TC-PAM16/32 also the new extended TC-PAM4/8/64/128 line coding. SHDSL allows symmetrical data and voice transmission at speeds up to 15Mbps over a single pair of copper. In addition, the Ittelecom SHDSL modem range also supports DSL channel bonding for up to 2 copper pairs in order to achieve speeds up to 30.4Mbps. An integrated 2 port Ethernet layer 2 managed switch with VLAN, QoS and RSTP support (10/100BaseT) ensures connectivity to IP services.

The ITTelecom Mini SHDSL.bis modems is a perfect solution for a wide range of applications in which IP services need to be transmitted over copper wires. The Mini SHDSL.bis product is a small-sized NTU unit with all the functionality included. Like all Ittelecom products the Ittelecom SHDSL modems are based on industrial components and manufactured according to highest quality standards providing additional value due to the extended temperature ranges and higher reliability. The combination of comprehensive functions providing maximum flexibility together with the higher quality of the Ittelecom SHDSL product family make it the perfect choice for all your DSL needs.

SERVICES:  
Guaranteed Warranty



Website: [ittelecom.co](http://ittelecom.co)  
Skype: [ittelecomco](https://www.skype.com/en/contacts/ittelecomco)  
Email: [mailto:sale@ittelecom.co](mailto:mailto:sale@ittelecom.co)

<https://ittelecom.co/shop/modem-sa-shdsl-2eth-2e1/>

# Modem SHDSL SA 2ETH 2E1



## Features & Benefits

|  |
|--|
| One or two pairs support   |
| Up to 15.2 Mbps data transmission per pair                                   |
| SHDSL and SHDSL.bis with TC-PAM4/8/16/32/64/128                              |
| Point-to-Point, Point-to-Multipoint & Ring Operation                         |
| Two Port Ethernet Switch (10/100BaseT )                                      |
| QoS, VLAN and RSTP Support   |
| Transparent Transmission of Modbus RTU/ASCII, DNP3 and IEC 60870.5 Protocols |
| Console Port, Telnet, Web, SNMP Management                                   |
| Included Primary Protection  |
| Robust DIN-Rail Metal Enclosure  |
| Smallest Size  |
| Extended Temperature option (-40°C... +80°C)                                 |
| Steel case   |

## Properties

|                             |   |
|-----------------------------|---|
| <b>DSL Version:</b>         | SHDSL / SHDSL.bis / Extended  |
| <b>Modulation:</b>          | TC-PAM16/32 and with Licence TC-PAM4/8/16/32/64/128   |
| <b>Data Rate:</b>           | 128kbps - 60.928Mbps, 4x 15.232Mbps   |
| <b>Copper Pairs:</b>        | 4 with Modes Master / Slave / Auto / Multipoint / Multipair   |
| <b>Interface:</b>           | 2x E1 (120Ohm), 2x Ethernet 10/100BaseT (Layer 2 Managed Switch)  |
| <b>Power:</b>               | 36 to 230VDC, accepts local and remote power, 5.3W Typ.<br>18 to 230VDC, no remote power when FG-PAM-SA4N-2E1B/2Eth-24V, V84E |
| <b>Physical Interfaces:</b> | RJ48 (E1), RJ45 (Ethernet), RJ48 (SHDSL), Molex (Power), DB9/USB (LCT)  |
| <b>Management</b>           | Console Port, Telnet, HTTP and SNMP   |
| <b>Temperature</b>          | Standard: -5 to +45°C, Extended: -20 to +80°C   |
| <b>Power Supply:</b>        | 90-260VAC option with FG-PAM-PA48G (not included)   |

SERVICES:  
Guaranteed Warranty



Website: [ittelecom.co](http://ittelecom.co)  
Skype: [ittelecomco](https://www.skype.com/en/contacts/ittelecomco)  
Email: [mailto:sale@ittelecom.co](mailto:mailto:sale@ittelecom.co)