



This device provides 32Channel telephone 1-4Channel E1 interface, 4Channel 1000M Ethernet interface (Wire speed 1000M) and 4 expansion interface. 4Channel Ethernet interface is switch interface, can support VLAN. 4 expansion interface can be used as the transmission channel of RS232/RS485/RS422 asynchronous data, voice signal, 2/4 line E&M audio signal, switch signal, Ethernet signal (Bandwidth 2M). SNMP or Console management is optional. It is very flexible.

## Features:

- Based on self -copyright IC
- E1 interface comply with G.703, adopts digital clock recovery and smooth phase-lock technology Voice port supports FXO and FXS port,
- Support FXO/FXS, EM2/4 audio, Magnet telephone Interface, FXO port docking with program-controlled switchboard, FXS port connected to the user's telephone;
- 1~32channel Voice access, supports caller ID feature and reverse polarity billing functions
- Support various sites mutual number allocation function
- Provide 4 expansion interface, you can extend 1~4Channel asynchronous data, such as RS232/RS485/RS422/Manchester code;1~4Channel voice, 1~8Channel switch or two/four line audio and so on
- Ethernet interface supports1000M, half/full duplex auto-adaptable, support VLAN
- 4Channel Ethernet interface is switch interface, support VLAN, can set to 4 channel logical isolation
- Ethernet interface can support AUTO-MDIX (crossed line and straightly connected line self-adaptable)
- Telephone interface with lightning protection, lightning reached IEC61000-4-5 Short circuit current wave 8 / 20μs, the peak output voltage 6KV open standards
- The transmission distance is up to 2-120Km without interruption
- AC 220V, DC-48V, DC24V can be optional

## Fiber

### Multi-mode Fiber

50/125um, 62.5/125um,

Maximum transmission distance:

Wave Length:

Transmitting power:

Receiver sensitivity:

Link budget:

5Km @ 62.5 / 125um single mode fiber,attenuation (3dbm/km)

820nm

-12dBm (Min) ~-9dBm (Max)

-28dBm (Min)

16dBm

### Single-mode Fiber

8/125um, 9/125um

Maximum transmission distance:

Transmission distance:

Wave Length:

Transmitting power:

Receiver sensitivity:

Link budget:

40Km

40Km @ 9 / 125um single mode fiber, attenuation (0.35dbm/km)

1310nm

-9dBm (Min) ~-8dBm (Max)

-27dBm (Min)

18dBm

## E1 Interface

Interface Standard:

Interface Rate:

Interface Code:

E1 Impedance:

comply with protocol G.703;

n\*64Kbps±50ppm;

HDB3;

75Ω (unbalance), 120Ω (balance);

Jitter tolerance: In accord with protocol G.742 and G.823 0~  
Allowed Attenuation: 6dBm

## ◆ Ethernet interface(10/100/1000M)

Interface rate: 10/100/1000 Mbps, half/full duplex auto-negotiation  
Interface Standard: Compatible with IEEE 802.3, IEEE 802.1Q (VLAN)  
MAC Address Capability: 4096  
Connector: RJ45, support Auto-MDIX

## ◆ FXS Phone Interface

Ring voltage: 75V  
Ring frequency: 25HZ  
Two-line Impedance: 600 Ohm (pick up)  
Return loss: 40 dB

## ◆ FXO Switch Interface

Ring detect voltage: 35V  
Ring detection frequency: 17HZ-60HZ  
Two-line Impedance: 600 Ohm (pick up)  
Return loss: 40 dB

## ◆ EM 2/4 Line

AD: 0dB  
DA: -3.5dB  
Two/Four-line Impedance: 600 Ohm  
Return loss: 20 dB

## ◆ Working environment

Working temperature: -10°C ~ 50°C  
Working Humidity: 5%~95 % (no condensation)  
Storage temperature: -40°C ~ 80°C  
Storage Humidity: 5%~95 % (no condensation)

Functional Description	32 * telephone, 4E1, 4*1000 Mbps Ethernet, Console or SNMP, Support 6U rackmount, One or Two Fiber interface, 4*RS232/422/485
Power	Power supply: AC180V ~ 260V ; DC -48V ; DC + 24V Power consumption: ≤10W
Dimension	Product Size: 485X138X45mm(WXDXH) 19 1U
Weight	2.5KG