



DAVID CLARK INDUSTRIAL HEADSET WITH PTT SWITCH

PN.: ITT-HS136

Web: www.iITTelecom.co

Phone: (+98) 21-22010560 Fax: (+98) 21-22035872

Address: Unit 3, No. 29, Ansari St., Northern Africa Blvd.
Tehran, Iran



HEADPHONE

- ◆ Type: Dynamic (F50)
- ◆ Frequency Response: 100Hz to 8 kHz
- ◆ Sensitivity: 95+/-5 dB SPL
(1 kHz, 1 mW input per earcup side)
full volume on ear simulator
- ◆ Impedance: 150 ohms
(300 ohms each; wired in parallel)
- ◆ Rate Input: 100mW
- ◆ Max. Input: 250mW

OVERVIEW

- ◆ Operating Temperature: -20 to 70 °C
- ◆ GA Use Dual plugs
- ◆ Super Soft Double Foam Head Pad
- ◆ Weights: 530g
- ◆ Molded cord assembly made to exceptional pull and flex standards
- ◆ Noise-canceling electret
- ◆ Strong Steel Boom provides flexibility and steady microphone placement
- ◆ Straight cord from headset to molded plug, 150CM
- ◆ Color: Black, green
- ◆ Noise Reduction Ratings (NRR): 24dB

MICROPHONE AND AMPLIFIER:

- ◆ Element Type: Noise-canceling electret
- ◆ Frequency Response: 100Hz to 5 kHz
- ◆ Operating Voltage: 8-32 Volts DC
- ◆ Matching Impedance: 150-1000 ohms
- ◆ Sensitivity: -33+/-4 dB