

Media Converter SFP4G2E Series Fiber Switch


P/N : [ITT-MC3852](#)



The ITT-SFP4G2E is a 10/100/1000Mbps adaptive gigabit Ethernet Fiber Switch. It has two 10/100/1000Mbps Ethernet ports and four 1.25Gbps fiber ports. Users can choose different SFP modules in need. It can extend the transmission distance; there are also many other advantages such as isolation protection, good data security, working stability and easy maintenance.



- Support the switch between 10/100/1000Base-T and 1000Base-SX/LX
- 4*1.25Gbps full-duplex fiber ports and 2*1000M Ethernet ports with auto-negotiation function
- Support MDI/MDIX and half/full-duplex with auto-negotiation function
- Each port has the complete LED Indicator light
- Support IEEE802.1d Spanning Tree
- Support IEEE802.1q and VLAN division
- Support high performance QoS function on each port
- Support 5-16V voltage input
- Require no configuration and will instantly operate as soon as you power it up
- Use Marvel chip, stable and reliable
- Low power consumption chip with heat sink built in to ensure longtime efficient operation



SERVICES:
Guaranteed Warranty



Standards	IEEE802.3 10Base-T IEEE802.3u 100Base-TX/FX IEEE802.3ab 1000Base-T IEEE802.3z 1000Base-SX/LX	IEEE802.3x Flow control IEEE802.1p QoS IEEE802.1d Spanning Tree IEEE802.1q VLAN
Certifications	CCC, CE, FCC, RoHS	
Ethernet Port	<ul style="list-style-type: none"> ➤ Connector: RJ45 ➤ Data Rate: 10/100/1000M ➤ Distance: 100m ➤ UTP Type: UTP-5E or higher level 	
Fiber Port	<ul style="list-style-type: none"> ➤ Connector: SFP slot ➤ Data Rate: 1.25Gbps ➤ Optical Wavelength: 850nm/1310nm/1490nm/1550nm ➤ Distance: 550m ~ 100km 	
Performance	<ul style="list-style-type: none"> ➤ Processing Type : Store and Forward ➤ MAC Table Size: 1K ➤ Buffer Space: 1Mbit ➤ Back bandwidth: 12G ➤ Time Delay: < 20μs 	
Power	<ul style="list-style-type: none"> ➤ Power type: external power supply ➤ Input Voltage: AC100V ~ 240V 50/60Hz ➤ Connector: DC Socket ➤ Working Voltage: 5V ➤ Power Consumption: 1.8W ~ 5W 	
Environment	<ul style="list-style-type: none"> ➤ Storage Temperature: -40~70°C ➤ Operating Temperature: -10~55°C ➤ Relative Humidity: 5-90% (no condensation) 	
Warranty	1 year	
Physical Characteristics	<ul style="list-style-type: none"> ➤ Dimension: 160×84×26mm ➤ Weight: 0.30kg ➤ Color: Metal, Black 	

SERVICES:
Guaranteed Warranty



Website: ittelecom.co


Skype: [ittelecomco](https://www.skype.com/en/contacts/ittelecomco)

Email: mailto:sale@ittelecom.co



Note:

1. Power supply provided by user or order additionally.
2. SC slot connector as default, FC/ST slot as request.



SERVICES:
Guaranteed Warranty

