

## 4 Ports Serial Device Server

P/N: ITT-MC4212



### Features:

- The 4 serial ports all support 3 serial forms: RS232, RS485, RS422.
- The 4 serial ports can independently full-duplex working, no interference between each other.
- Support extension function, can extending up to 32 serial ports.
- Rich signal lights, each port has self TCP connecting indicator and data activity indicator.
- Support power supply via cable ----POE power supply.



ITT-LAN5400 serial device server is a 4 ports protocol converter between RS232/485/422 and TCP/IP launched by Ittelecom Information Technology Co., LTD.

ITT-LAN5400 support four RS232 serial ports and RS422/485 serial ports, connecting to the ITT-LAN5400 via a cable can realize four serial ports full-duplex work at the same time, the function of each serial ports are the same as ITT-LAN5102/ITT-LAN5103, is the ideal choice of the multi-serial port connecting to the Internet.

ITT-LAN5400 support extending to 8 serial ports, 12 serial ports and 16 serial ports via the cascade Ethernet port, which can be extended to 32 serial ports.



SERVICES:  
Guaranteed Warranty



## Interface:

<b>Network Interface</b>	<ul style="list-style-type: none"> <li>➤ Ethernet: 10/100 Mbps, RJ45</li> <li>➤ Protection: 2KV electrical plus protection</li> </ul>
<b>Serial Interface</b>	<ul style="list-style-type: none"> <li>➤ Port: RS-232/485/422</li> <li>➤ Serial Port: 4</li> <li>➤ Parity: None, Even, Odd, Space, Mark</li> <li>➤ Data Bite: 5 ~ 9</li> <li>➤ Stop Bit: 1,2</li> <li>➤ Flow Control: RTS/CTS, DTR/DCR, XON/XOFF</li> <li>➤ Baud Rate: 1200bps ~ 460800bps (Can be customized to 1M or 1.5M)</li> </ul>
<b>Software</b>	<ul style="list-style-type: none"> <li>➤ Protocol: TCP, HTTP, UDP, ICMP, ARP, IP, DNS, DHCP</li> <li>➤ Virtual Serial Port Platform: Windows 98/2000/XP/WIN7/WIN8</li> <li>➤ Configure Method: Web Brower, serial like-AT command</li> </ul>
<b>Mechanical Properties</b>	<ul style="list-style-type: none"> <li>➤ Voltage Input: DC9 ~ 24V, 45mA</li> </ul>
<b>Mechanical Properties</b>	<ul style="list-style-type: none"> <li>➤ Shell Material: Anti-electromagnetic material SECC steel plate</li> <li>➤ Size: L×W×H=9.4cm×6.5cm×2.5cm</li> </ul>
<b>Work Environment</b>	<ul style="list-style-type: none"> <li>➤ Work Temp., Humidity: -30 ~ 85°C, 5 ~ 95% RH</li> <li>➤ Storage Temp., Humidity: -30 ~ 85°C, 5 ~ 95% RH</li> </ul>
<b>Fiber-optic Cable</b>	<ul style="list-style-type: none"> <li>➤ 50/125μm or 62.5/125μm multi-mode fiber cable, up to 220/550m.</li> <li>➤ 8/125, 8.7/125,9/125μm single-mode cable, providing long distance for 10/20/40/60/80km/100km</li> </ul>
<b>Certifications:</b>	<ul style="list-style-type: none"> <li>➤ CE, FCC, RoHS</li> </ul>

SERVICES:  
Guaranteed Warranty

