


Ethernet Switch 8 port Ethernet PoE - 2 SFP Modules



Introduction	Image
<p>This managed industrial Ethernet switch is designed to match the critical industrial standards. With reliable and simple operation against vibration and shock, and wide operation temperature range, it could match a variety of harsh environment. The switch complies with CE and FCC standards, and passed the 100% burning test to ensure that it will fulfill the needs of industrial applications. It is a good choice for an economical solution for industrial Ethernet connections.</p>	

Properties	
Standard	IEEE 802.3 10 Base-T and IEEE 802.3u 100 Base-TX, IEEE802.3z, IEEE802.3ab
Topology	STAR
Number of Ports	8x 10/100/1000-TX ports 2 SFP Modules
Transmission Rate	TP: 10/100/1000 Mbps
Switching mode	Store and Forward
LED Indicator	LED status of Link, activity, Full/half duplex, speed, and power on diagnostic function
Speed	Twisted-pair: 10/20Mbps for half/full-duplex 100/200Mbps for half/full duplex 2000Mbps for full-duplex
Power supply	AC:220V or DC:-48V
Temperature	-20°C to 70°C ~ -40°C to 75°C
Humidity	5% to 95% RH

Physical Characteristics
Housing: Aluminum Alloy material with IP40 Protection
Dimension: 138mm(L) X 112mm(W) X 60mm(H)
Weight: 710g
Installation: Din-Rail mounting, Wall mounting

Features & Benefits
8 10/100Base-T(X) ports and 2 1000Base-X ports
"OP-Ring" (recovery time<20ms), RSTP/STP, and MSTP for network redundancy
SNMPv3, IEEE802.1X, HTTPS and SSH to enhance network security
Port-based VLAN, IEEE802.1Q VLAN and GVRP to ease network planning
DHCP Option 82 for IP address assignment with different policies
Ethernet/IP and Modbus/TCP industrial Ethernet protocol supported
Bandwidth management prevents unpredictable network status
RMON for efficient network monitoring and proactive capability
Lock port allows access by only authorized MAC addresses
Port mirroring for online debugging
Automatic warning by exception through email, relay output
QoS and ToS/DiffServ for flow control and management
IEEE 802.3ad, LACP for optimum bandwidth utilization
Configurable by CLI for advanced management function
-40°C-85°C operating temperature range

SERVICES:
Guaranteed Warranty

