

UmManaged Industrial Ethernet Switch 8 ETH (10/100/1000) 2 SFP (1.25G)


P/N : [ITT-SW3948](#)



- 12-36VDC wide voltage range power inputs
- As low as 6 watts load power consumption
- -40 to 85°C operating temperature range
- IP40 protection class with metal housing
- Fanless design
- Level 4 EMC Protection

The ITT-8GE2GF-I-DC provides 8*10/100/1000 Base-T electrical ports and 2*1000Base-X optical ports. All models are with IP40 protection class and meet EMC industrial level 4 requirements. It provides 12-36 VDC wide voltage range power inputs, DIN rail mounting, wide operating temperature range of -40 to the +85°C. In addition to its compact size for space-saving installation, each product has passed a 100% burn-in test in 85°C to ensure its quality.

All of these features make the product ideal for applications that require high-reliability transmission, such as video surveillance, tolling systems, ITS, and factory automation.



SERVICES:
Guaranteed Warranty



UnManaged Industrial Ethernet Switch

Network Standards	IEEE 802.3 10Base-T IEEE 802.3u 100Base-Tx IEEE 802.3ab 1000Base-T IEEE 802.3z 1000Base-X
Certifications	CCC, CE, FCC, RoHS
Switch Technical	<ul style="list-style-type: none">➤ MAC Table: 16K➤ Packet Buffer: 2M➤ Packet Forwarding Rate: 14.88Mpps➤ Switching Delay: <5us
Interface	<ul style="list-style-type: none">➤ Optical Ports: 2 1000Base-X (SFP)➤ Electrical Ports: 8 10/100/1000Base-T (RJ45)
LED indicator	<ul style="list-style-type: none">➤ Power LED: PWR➤ Interface LED: RJ45(Link&ACT) , Fiber(Link&ACT)
MTBF	360,000 hrs
Machinery Standard	<ul style="list-style-type: none">➤ IEC60068-2-6 (Vibration)➤ IEC60068-2-27 (Shock)➤ IEC60068-2-32 (Free Fall)
Power	<ul style="list-style-type: none">➤ Power Terminal: 4-pin 5.08mm-spacing plug-in terminal block➤ Full load power consumption: < 6W➤ Overload Protection: Support➤ Reverse Connection Protection: Support Redundancy Protection: Support
Physical	<ul style="list-style-type: none">➤ Housing: Metal, fanless➤ Protection Class: IP40➤ Dimensions : 45mmx100mmx175mm(W×H×D)➤ Weight: 0.8kg➤ Mounting: DIN-Rail or Panel mounting
Environment	<ul style="list-style-type: none">➤ Operating Temperature: -40 to 85°C➤ Storage Temperature: -45 to 85°C➤ Ambient Relative Humidity: 5 to 95% (non-condensing)


SERVICES:
Guaranteed Warranty



Industrial Standard	<ul style="list-style-type: none"> ➤ EMI: ➤ FCC CFR47 Part 15, EN55022/CISPR22, Class A ➤ EMS: ➤ IEC61000-4-2 (ESD): ±8kV (contact), ±15kV (air) ➤ IEC61000-4-3 (RS): 10V/m (80MHz-2GHz) ➤ IEC61000-4-4 (EFT): Power Port: ±4kV; Data Port: ±2kV ➤ IEC61000-4-5 (Surge): Power Port: ±2kV/DM, ±4kV/CM; Data Port: ±2kV ➤ IEC61000-4-6 (CS): 3V (10kHz-150kHz); 10V (150kHz-80MHz) ➤ IEC61000-4-16 (Common mode conduction): 30V (cont.), 300V (1s)
---------------------	---


Product model	ITT-8GE2GF-I-DC
Product descriptions	8*10/100/1000BaseT Switches , Din-Rail and Wall m-T+2*1000Base-X (SFP), Unmanaged Industrial Ethernet installation, 12-36VDC power input .

Power Terminal




- 4pin 5.08mm-spacing plug-in terminal
- 12V-36VDC wide voltage input
- P1&P2 dual power input
- Reverse protection

Din-Rail



Earth Protection



Ground screw

Wall mounting



SERVICES:
Guaranteed Warranty

