



Features:

- 4*10/100/1000Base-TX PoE port (Data/Power)
2*1000M SFP
- CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS

ITT-SWP4850 is gigabit RJ45 and SFP uplink unmanaged PoE switch independently developed by ittelecom, which can automatically detect the compliance with IEEE802.3af/at | PoE +| HiPoE standard power receiving equipment and power supply, new integrated hipoe and poedog function, solve the power supply problem of high-power outdoor ball machine, high-power wireless AP and other high-power equipment, pogdog function will realize the automatic repair of PD end equipment when it accidentally crashes, solve the time-consuming and labor-consuming problem of human operation, and realize intelligent unattended.

Port performance

- Provide 4*10/100/1000M PoE RJ45 adaptive ports, all of which can realize line speed forwarding.
- Provide 2 gigabit SFP uplink ports for high-speed uplink transmission.
- Each port supports MDI / mdix auto flip and duplex / rate self negotiation.
- Support IEEE 802.3x full duplex flow control and backpressure half duplex flow control.

Special function

- Hipoe: the first port outputs 60W to solve the power supply problem of high-power PD. It can connect large ball machine, wireless AP or intelligent door lock and other high-power PoE devices.
- Poedog: when PoE is started, it detects the status of PoE electrical equipment in real time; when the equipment side is abnormal, the switch actively sets the port and restores PoE power supply to realize unattended.

PoE power supply function

- According to IEEE 802.3af/at PoE power supply standard, the maximum PoE output power of the whole machine is 65W, single port for the maximum PoE output power is 30W(First port can be max 60W)
- Automatic identification of PoE equipment for power supply without damaging non PoE equipment.

Three working modes

- N -- standard switching mode: all ports communicate freely, suitable for common data transmission environment.

- V - port isolation mode: the downlink ports are isolated from each other, which is suitable for the use scenarios of connecting wireless AP, suppressing network storm and improving network performance.
- C -- flow control mode: port flow balance control, prevent big data flow packet loss, ensure the efficient and stable operation of user network.

The equipment is stable and reliable

- ITTelecom independent research and development of power supply, high redundancy design, to provide long-term stable PoE power output.
- The equipment meets the national CCC standard, fully meets the safety requirements, and is safe and reliable.

Easy to use

- Plug and play.
- Dynamic LED indicator provides simple working status prompt and troubleshooting.

Complete set of accessories

- By default, the switch is equipped with an AC power cord.

Technical Parameters:

• Fixed Port	➤ 4*10/100/1000Base-TX PoE port (Data/Power) ➤ 2*1000M SFP
• PoE Ports	➤ 1-4 port supports PoE(optional first port outputs HiPoE_60W)
• Function	➤ N:(Standard normal) ➤ V:(Port isolation) ➤ C:(Flow Control mode) (specific port refers to user manual)
• Network Protocol	➤ IEEE 802.3 ➤ IEEE 802.3i 10BASE-T ➤ IEEE 802.3u 100BASE-TX ➤ IEEE 802.3ab1000BASE-T ➤ IEEE 802.3x ➤ IEEE 802.3z 1000BASE-X ➤ IEEE 802.3af/at
• PoE Standard	➤ IEEE802.3af/at
• Port Specification	➤ 10/100/1000BaseT (X) Auto
• Transmission Mode	➤ Store and Forward(full wirespped)
• Bandwidth	➤ 16Gbps
• Packet Forwarding	➤ 14.44Mpps
• MAC Address	➤ 2K
• Buffer	➤ 2.5M

• Transmission Distance	<ul style="list-style-type: none"> ➤ 10BASE-T : Cat3,4,5 UTP(≤250 meter) ➤ 100BASE-TX : Cat5 or later UTP(150 meter) ➤ 1000BASE-TX : Cat6 or later UTP(150 meter) ➤ 1000BASE-SX:62.5μm/50μm MMF(2m~550m) ➤ 1000BASE-LX:62.5μm/50μm MM(2m~550m) or 10μm SMF(2m~5000m)
• Power Pin	➤ Default 1/2(+), 3/6(-); Optional order4/5(+), 7/8(-)
• Single port power	➤ Average 15.4W; MAX 30W
• Total power/Input voltage	➤ MAX 80W (AC100-240V 50/60HZ)
• Watt	➤ Standby Power Consumption: ≤8W;
• LED Indicator	<ul style="list-style-type: none"> ➤ Power: Power LED(optional over-power LED) ➤ 5 6:(SFP LED) ➤ Port:(Orange=PoE LED+Green=Link LED)
• Power Input	➤ Built-in power AC: 100~240V 50-60Hz 1A
• Operating Temperature/Humidity	➤ -10~+55°C; 5%~90% RH Non coagulation
• Storage Temperature/Humidity	➤ -40~+75°C; 5%~95% RH Non coagulation
• Product size/Packing size (L*W*H)	<ul style="list-style-type: none"> ➤ 210mm*150mm*35mm ➤ 270*mm220mm*68mm
• N.W/G.W (kg)	➤ 0.7kg/1.1kg
• Installation	➤ Desktop(optional wall and machine hanger parts)
• Lightning protection level	<ul style="list-style-type: none"> ➤ IP30 ➤ 3KV 8/20us;
• Certificate	➤ CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;