

Features:

- 8*10/100/1000Base-TX PoE port (Data/Power)
- 2*10/100/1000Base-TX uplink RJ45 port (Data)
- CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS



ITT-SWP4854 is 8*10/100/1000M+2*10/100/1000M unmanaged PoE switch independently developed by Ittelecom, which can automatically detect the compliance with IEEE802.3af/at | PoE +| HiPoE standard power receiving equipment and power supply, new integrated hipoe and poedog function, solve the power supply problem of high-power outdoor ball machine, high-power wireless AP and other high-power equipment, poedog function will realize the automatic repair of PD end equipment when it accidentally crashes, solve the time-consuming and labor-consuming problem of human operation, and realize intelligent unattended.

Port performance

- Provide 8*10/100/1000M PoE RJ45 adaptive ports, all of which can realize line speed forwarding.
- Provide 2*10/100/1000M RJ45 uplink ports for high-speed uplink transmission.
- Each port supports MDI / mdix auto flip and duplex / rate self negotiation.
- Support IEEE 802.3x full duplex flow control and backpressure half duplex flow control.

Special function

- Hipoe: the first port outputs 60W to solve the power supply problem of high-power PD. It can connect large ball machine, wireless AP or intelligent door lock and other high-power PoE devices.
- Poedog: when PoE is started, it detects the status of PoE electrical equipment in real time; when the equipment side is abnormal, the switch actively sets the port and restores PoE power supply to realize unattended.

PoE power supply function

- According to IEEE 802.3af/at PoE power supply standard, the maximum PoE output power of the whole machine is 65W, single port for the maximum PoE output power is 30W(First port can be max 60W)
- Automatic identification of PoE equipment for power supply without damaging non PoE equipment.

Three working modes

- N -- standard switching mode: all ports communicate freely, suitable for common data transmission environment.
- V - port isolation mode: the downlink ports are isolated from each other, which is suitable for the use scenarios of connecting wireless AP, suppressing network storm and improving network performance.
- C -- flow control mode: port flow balance control, prevent big data flow packet loss, ensure the efficient and stable operation of user network.

The equipment is stable and reliable

- Ittelecom independent research and development of power supply, high redundancy design, to provide long-term stable PoE power output.
- The equipment meets the national CCC standard, fully meets the safety requirements, and is safe and reliable.

Easy to use

- Plug and play.
- Dynamic LED indicator provides simple working status prompt and troubleshooting.

Complete set of accessories

- By default, the switch is equipped with an AC power cord, a manual.

Technical Parameters:

• Fixed Port	<ul style="list-style-type: none"> ➢ 8*10/100/1000Base-TX PoE port (Data/Power) ➢ 2*10/100/1000Base-TX uplink RJ45 port (Data)
• PoE Ports	➢ 1-8 port supports PoE(optional first port outputs HiPoE_60W)
• Function	<ul style="list-style-type: none"> ➢ N:(Standard normal) ➢ V:(Port isolation) ➢ S:(Super mode)(specific port refers to user manual) ➢ Ai version:PoE auto execution、detection and resets fault device,when PoE is on.
• Network Protocol	<ul style="list-style-type: none"> ➢ IEEE 802.3 ➢ IEEE 802.3i 10BASE-T ➢ IEEE 802.3u100BASE-TX ➢ IEEE 802.3x ➢ IEEE 802.3af/at/PoE++ ➢ Ittelecom HiPoE
• PoE Standard	➢ IEEE802.3af/at , (AI version,first port supports Hipoe)
• Port Specification	➢ 10/100/1000BaseT (X) Auto
• Transmission Mode	➢ Store and Forward(full wirespped)
• Bandwidth	➢ 2Gbps

• Packet Forwarding	➤ 1.44Mpps
• MAC Address	➤ 1K
• Buffer	➤ 768M
• Transmission Distance	➤ 10BASE-T : Cat3,4,5 UTP(≤250 meter) ➤ 100/1000BASE-TX : Cat5 or later UTP(150 meter)
• Power Pin	➤ Default 1/2(+), 3/6(-); Optional order4/5(+), 7/8(-)
• Single port power	➤ Average 15.4W; MAX 30W (Ai version:MAX 60W)
• Total power/Input voltage	➤ MAX 120W (AC100-240V 50/60HZ)
• Watt	➤ Standby Power Consumption: <3W; ➤ Full-load Power Consumption: <65W
• LED Indicator	➤ P:Power LED(over-power LED) ➤ Uplink:(Link LED=10/100M Link) ➤ Port:(Orange=PoE LED+Green=Link LED) ➤ V:(Port isolation LED) ➤ S:(Super mode LED)
• Power Input	➤ Built-in power AC: 100~240V 50-60Hz 1A
• Operating Temperature/Humidity	➤ -10~+55°C; 5%~90% RH Non coagulation
• Storage Temperature/Humidity	➤ -40~+75°C; 5%~95% RH Non coagulation
• Product size/Packing size (L*W*H)	➤ 210mm*150mm*35mm ➤ 270*mm220mm*68mm
• N.W/G.W (kg)	➤ 0.8kg/1.2kg
• Installation	➤ Desktop (optional wall +machine hanger parts)
• Lightning protection level	➤ IP30 ➤ 3KV 8/20us;
• Certificate	➤ CE mark, commercial; CE/LVD EN60950; FCC Part 15 Class B; RoHS;